

2021 Mudd-Ox 6 Wheel Amphibious Trailer

Chassis & Body

Frame	Powder coated steel for long life and durability
Axles	1500" Diameter Axles
Tires	26" x 14" x 12" Mudd-Ox Vendetta on 12" Mudd-Ox Beadlock Rim.
Floor Board	Wooden with handles for quick removal
Body	Vacuum formed lower body and optional skid plate, made from High Molecular Weight Polyethylene (HMWPE)

Performance

Towing Speed - Land	Maximum 30 mph [A]
Towing Speed - Water	Maximum 10 mph [B]
Load Capacity	2,000 lbs. (907 kg) (distributed evenly) Less the weight of any accessories [C][F]
Approach and Departure Angles	25° Maximum

Safety

Safety	Optional Roll Over Protection System with a roll bar on each end of the trailer.
Usage Conditions	All weather, all terrain, -40°F to +110°F (-40°C to +43°C)

Max ATV Australia
PO Box 1652
Berrimah, NT 0828
Phone: 0412 015 144
Fax: 260-768-3074
www.muddox.net
wayne@maxatv.com.au



Custom Colors Available Upon Request



Ground Clearance & Ground Pressure

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 1 psi [D] Tracks: 0.25 psi [D]

Weight & Dimensions

Weight	750 lbs
Outer Dimensions	168" long w/ hitch, 123" long w/o hitch x 82" wide x 35" high on 26x14x12" Vendetta Tires
Inner Dimensions	100" long at bottom, 119" long at top x 33" wide at bottom, 56" wide at top x 16" high. Fenders 12" wide (included in 56" wide at top measurement).

Warranty

Warranty	1 year [E]
----------	------------

Specifications are subject to change without notice.

- [A] Top speed depends on terrain conditions and drive train options.
 [B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)
 [C] See Owner's manual for accessory listing and weight.
 [D] Depending on weight of cargo and accessories onboard
 [E] See Vehicle Owner's Manuals for full warranty information.
 [F] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

Bearing Grease Zerk Relocation	Tire - Dual Wheel Kit
Rescue	Tracks - 20" Wide Ripsaw
Skid Plate	Transport Tie Downs
Safari Rack (Full/Half Length)	Twin Roll Bars

Ver 200106

