

2021 Mudd-Ox 8x8 XL

Engine

	Gasoline EFI	
Type	XL40	XL57
Model	Briggs & Stratton	Kubota
Brand	40 HP / 30 kW	57 HP / 42 kW
Power Output	58.5 lbs. / 79.3 Nm	86.7 lbs. / 117.5 Nm
Torque	993 cc	1537 cc
Displacement	Air-Cooled	Liquid-Cooled
Cooling	50 Amp, 105 Opt	105 Amp
Electrical	65 Series	
Battery		

Transmission

Transmission	Mudd-Ox Hydrostatic
Brakes	Hydrostatic and Hydraulic Braking

Controls & Instrumentation

Steering	Ergonomic Left and Right Steering Controls
Parking Brake	Ratchet Style Mechanical
Instrumentation	Full Instrumentation Dash Panel
Gauges	Full Engine Power View & Diagnostics (XL57) Fuel Gauge Volt Meter Hour Meter Coolant Temperature (XL57) Hydraulic Temperature
Warning Lights	Check Engine Low Oil Pressure Neutral Light Parking/Emergency Brake

Chassis, Body & Lights

Frame	Powder coated steel for long life and durability
Drive System	#60-2 (Twin 60) Roller Chain
Axles	1.500" Solid Steel
Body	Vacuum formed upper body, lower body and skid plate, made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" x 12" Mudd-Ox Vendetta on 12" Mudd-Ox Bead Lock Rim
Lighting	LED Headlights & LED Tail Lights LED Brake & Reverse Lights w/ Optional Steering Wheel

Performance

Speed - Land	17-25 mph (27-40 km/h) [A]
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	2,000 lbs. (907 kg)(distributed evenly) Less the weight of any accessories [C]
Load Capacity - Water	1,000 lbs. (454 kg)(distributed evenly) Less the weight of any accessories [C]
Turning Circle	Zero turning radius, machine counter-rotates
Towing Capacity	2,500 lbs. (1,134 kg) [G]
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]
Rear Bench Seat	Optional

Max ATV Australia
PO Box 1652
Berrimah, NT 0828
Phone: 0412 015 144
www.maxatv.com.au
wayne@maxatv.com.au



Safety

Safety	Fold down Roll Over Protection System with seat belts for front two passengers. Rear Roll Over Protection System is available as an option. Mudd-Ox Hydrostatic precision control drive system enables safe control at all times while maneuvering in the most difficult terrains.
Fuel Capacity	12 US Gallons giving approx. 8-10 hours of operation 10.5 US Gallons with optional Rear Roll Bar
Operating Conditions	All weather, all terrain, -40°F to +110°F (-40°C to +43°C)

Ground Clearance

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 2 psi [D] Tracks: 0.5 psi [D]

Operation & Convenience

Self-Extraction Winch	5,000 lb. Capacity
Storage	Lockable glove box, Built in Cup Holders 12.5" x 28" Insert area over Engine Cover
Electrical Output	12V Outlet, Dual Port USB Outlet
Bilge Pump	Standard

Weight & Dimensions

Shipping Weight	2,190 lbs. XL40	2,290 XL57
Dimensions	123" Long 68" Wide 79" High with Roll Bar Up, 61" High with Roll Bar Down (on 26 x 14 x 12" Vendetta Tires)	
Approach and Departure angles	25° Maximum	

Warranty

Warranty	1 year or 500 hours limited warranty on Mudd-Ox Engine: See manufacturer's manual [E]
----------	---

Specifications are subject to change without notice.

[A] Top speed depends on terrain conditions and drive train options.

[B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)

[C] See Owner's manual for accessory listing and weight.

[D] Depending on weight of person, cargo and accessories onboard

[E] See Owner's Manual for full warranty information.

[F] Provides better flotation and allows for more carrying capacity in the water.

[G] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

A/C Unit	Outboard Motor
A/C Unit Brush Guard	Rear Accessory Carrier - Main Mount
Automatic Chain & Bearing Lubrication	Rear Seat - Standard
Auxiliary Switch Panel	Rear Seat - Bench
Auxiliary Hydraulics	Rescue
Bearing Grease Zerk Relocation	Safari Rack (Full/Half Lengths)
Brush Cage (Full/Half Length)	Snow Plow - 85"
Brush Guard	Snow Plow - Boss V Blade
Cab - Aluminum	Spare Carrier - 5 Gallon Fuel Can
Cab - Canvas (Full/Half Combo)	Spare Carrier - Tire
Cab - Canvas (Rear Enclosure)	Tire - 26x18 x12" Vendetta
Cab - Stereo Kit	Tire - Dual Wheel Kit
Cab - Windshield Cover	Tool Box
Controls - Steering Wheel (XL57)	Tracks - 16" Wide Adair
Cargo Liner	Tracks - 20" Wide Chevron
Cargo Platform	Tracks - 20" Wide Ripsaw
Dump Bed	Tracks - 21" Wide Beaver Dam
Engine Remote Oil Drain	Transport Tie Downs
Fender Kit	Twin Roll Bar Package
Float - Catwalk	Winch - Synthetic Rope
Float - Front	Winch - 5000 lbs. Rear Mount
Fuel Fill - Rear	Windshield
Heater w/ Defrost	Windshield Wiper
Light Bar 10-50"	

Ver 200108